

LIGHT COMPLET

Watertight junction boxes

Watertight junction boxes with assembled and wired power sockets



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG					(A)	(V)
40892	Knock-out entries	0.20	1	Schuko-type socket	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 108x108x64 mm.

BOX: EX111.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG					(A)	(V)
41493	Plain sides	0.39	2	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 162x116x76 mm.

BOX: EL161.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG					(A)	(V)
41045	Plain sides	0.39	1	Sloping flush-fit socket	44	3P+N+E	16	400
			1	Schuko-type socket	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 162x116x76 mm.

BOX: EL161.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG					(A)	(V)
40427	Plain sides	0.58	4	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 175x151x95 mm.

BOX: EL171.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG					(A)	(V)
40936	Plain sides	0.56	1	Sloping flush-fit socket	44	3P+E	16	400
			2	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 175x151x95 mm.

BOX: EL171.

IP44 unit protection.

Halogen-free materials. Any assembly combination can be supplied, with no minimum order quantity

Watertight junction boxes with assembled and wired power sockets



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG						
							(A)	(V)
41177	Plain sides	1.08	6	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 241x180x95 mm.

BOX: EL231.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG						
43377	Plain sides	0.70	1	Sloping flush-fit socket	44	3P+N+E	16	400
			2	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 241x180x95 mm.

BOX: EL231.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG						
42054	Plain sides	1.28	2	Sloping flush-fit sockets	44	3P+N+E	16	400
			2	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 241x180x95 mm.

BOX: EL231.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG						
43322	Plain sides	0.82	1	Sloping flush-fit socket	44	3P+N+E	16	400
			3	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 241x180x95 mm.

BOX: EL231.

IP44 unit protection.



Ref. No.	Description	Weight	Components					
			No.	Description	IP	Poles	I	Voltage
		KG						
42209	Knock-out entries	0.94	1	Sloping flush-fit socket	44	3P+E	16	400
			1	Sloping flush-fit socket	44	3P+N+E	16	400
			3	Schuko-type sockets	44	2P+E	16	230

FINISH: Base and cover in PS RAL 7035 grey.

DIMENSIONS: 241x180x95 mm.

BOX: EX231.

IP44 unit protection.

Boxes assembled and wired according to the REBT
(Low Voltage Electricity Regulation)